

Specification

Items	Data
Power supply	DC 5V
Electric current	500mA-800Ma
Av out impedance	75 Ω
Av out volt	1Vp-p
TV Mode	PAL/NTSC
Internal Camera	SONY 1/3CCD (Optional)
Trigger for record	Motion detection
Trigger for alarm	Motion detection +PIR detection (optional)
PIR detection distance	$\leq 8M$
View angle	≤ 120 degree
Record Frame	PAL:10+/s NTSC:10f/s (have 5f/s made for order
AVI Resolution	320 x 240
JPEG resolution	640 x 480
Horizontal resolution	420TV Line
Memory	Flash memory and SD Card
SD card capacity	$\leq 2G$ byte
OSD	English
Alarm chip	Fixed code:PT2262/Study code:SC1527
Surge resistance	4.7M Ω (optional)
Date code	D1 low , D2 high , D3 empty , D4 empty
Wireless frequency	315NHZ/433MHZ (optional)
Li-battery Capacity	1800NAH
Battery recharge	>6 hours
Battery discharge	>3 hours
AC adapter	AC/110-240v , 50-60HZ , DC5V , 1.5A
RC distance	$\leq 8M$
IR distance	5M-8M
IR wavelength	850M
2G SD card using time	Common conditions: AVL video recording for 3-5days. Snapshot for 15days